

UNITECH

International (Pvt) Ltd.

15-YEAR LICENSED MANUFACTURING
PARTNERS WITH **PACKO-INOX**

VM/DX 200L & 300L



DIRECT EXPANSION COOLING | HYGIENIC | ENERGY EFFICIENT | ISO 5708 COMPLIANT

DESIGNED FOR SMALL TO MEDIUM DAIRY SHOPS REQUIRING **FAST COOLING, HYGIENIC MILK STORAGE, AND RELIABLE OPERATION.** USING DIRECT EXPANSION TECHNOLOGY, THE SYSTEM COOLS MILK RAPIDLY WHILE MAINTAINING UNIFORM TEMPERATURE AND PRESERVING MILK QUALITY.



TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Model	VM/DX 200 - VM/DX 300
Milk Holding Capacity	230 LITRES - 338 LITRES
Construction (inner/outer)	AISI Stainless Steel 304
Insulation	PUF (CFC free)
Temperature Control	100% Automatic through digital Milk Temperature Controller (Emerson-EU)
Agitation	100% Automatic Agitator motor by UNITECH
Cooling Machine	1 HP - 1.25 HP
Ampere Consumption	4.4A - 6.4A
Evaporator	AISI Stainless Steel 304-Laser Welded (Pillow Plate Heat Exchanger)
Condenser	ACR Copper Tubes-Aluminium Fins
Dimensions	(L x W x H) 1080mm x 1080mm x 1230mm / 1260mm x 1260mm x 1205mm
Weight (Dry)	140 Kg - 170 Kg

ISO 5708 COMPLIANCE

- ENGINEERED AND MANUFACTURED IN ACCORDANCE WITH THE GLOBAL BENCHMARK FOR BULK MILK COOLERS.
- MANUFACTURING BASED ON EUROPEAN DESIGN PRACTICES.
- FACTORY QUALITY CONTROL & TESTING BEFORE DISPATCH.

IDEAL FOR

- DAIRY SHOPS
- SMALL DAIRY FARMS
- RETAIL OUTLETS
- COMMERCIAL MILK PRODUCERS
- EXPORT-ORIENTED DAIRY OPERATIONS

TRUSTED BY LEADING DAIRY PROCESSORS IN PAKISTAN AND INTERNATIONAL MARKETS

